



OKI



PLAVI

Colour LED Label Printer

Pro1040/1050

Innovation in Label Printing



Professional Colour Label Printer

Grow Your in-house Label Printing with Just-in-time Creation and affordable cost

Wide range of media handling | Weatherability | CMYK + Spot color white |
High resolution LED printhead | Low TCO | Variable data printing |
Roll-to-roll and roll to sheet printing

*Re-winder attachment for Roll-to-roll printing is optional accessory



Specification Summary

Product Name		Pro1050	Pro1040
Material Number		46672103	46672003
EAN Code		5031713072003	5031713071990
Printer Mechanical Section	Printing Method	Digital 5 LED full-colour electrophotographic printing method	
	Print Speed *1	Max. 152.4mm/s (6ips)	
	Minimum Print Margin	Top: 2.12mm, Bottom: 2.12mm, Right: 2.12mm, Left: 2.12mm	
	Print Resolution	1200 × 1200 dpi, 600 × 600 dpi	
	Media Format	Roll	
	Roll Outer Diameter	203.2mm (8")	
	Core Inner Diameter	76.2mm (3")	
	Media Width	Roll paper: 25.4mm(1.0")- 130mm (5.1") including liner	
	Label Length per job	12.7mm - 1320.8mm	
	Print Width	25.4mm - 126.0mm	
	Max Print Width	125.76mm(4.95")	
	Cut Length	Min. 101.6mm(4")	
	Media Type	Plain Paper, Film, Plain Paper Label, Glossy Paper Label, Synthetic Film Label	
	Media Thickness	0.076 - 0.250mm	
	Roll Wind Direction*3	Face-out, Face-in	
Control Unit	Media Detection	Black Mark (printed on back of liner), Gap, None *4	
	Media Sensor	Thru-Beam Type, Reflective Type	
	Auto Cutter	Full Cut	
	Recommended Daily Duty Cycle	Max. 8,000 pages per day *5	
	Memory (Std./Max)	2GB/2GB	
	Interface	USB	
		LAN	
	Protocol	TCP/IP	
	Printer Language	Adobe PostScript 3, PCL 5c emulation, PCL 6 (XL) emulation	
	Font	Adobe PostScript 136 fonts, PCL emulation 81 scalable fonts, 4 bitmap fonts	
Other Specifications	Power Source *6	Single phase 230V AC +/-10%, 50/60 Hz +/-2%	
	Power Consumption	Operating	
		Max. 1200W / Ave. 710W	
		Idle	
		Ave. 27W	
	Power Save	25W or below	
		Operating Environment	
		Operating: 10 - 30 °C, 20 - 70 %RH, Storage: -10 - 43 °C, 10 - 90 %RH, No condensation	
	Dimensions (WxDxH) *7	1040×477×441mm	
	Weight (includes supplies)	Approx. 62kg (Printer with unwinder)	Approx. 61kg (Printer with unwinder)
	Weight (excludes supplies)	Approx. 50kg(Printer with unwinder)	
	Supported OS *8	Windows 10, Windows 8.1, Windows 8, Windows 7, Windows Server 2016, Windows Server 2012 R2, Windows Server 2012, Windows Server 2008 R2, Windows Server 2008	
	Safety & Environment	RoHS, Network Access License, cUL Mark, cULus Mark, UL Mark, CSA Mark, EMC-Directive, CE Mark, GS Mark	
	Product Life	5 years or 6 million pages *9	
	In The Box	Power cable, DVD-ROM (Software Drivers & Manuals)	

*1 Print speed may vary depending on media size, type and thickness. *2 Please test your media in prior to use. Print Quality may vary depending on media and some media may cause damage on device. *3 Face-out or face-in can not change after installing. *4 Please put a black mark on the back side of media / liner. An internal sensor cannot detect a black mark on print side. *5 A6 continuous printing based. In case exceeding 8,000 pages per day, it might impact the print quality. *6 Uninterruptible Power System/UPS and a inverter use is not galanteed. There is a risk of fire. *7 Exclude a protruding object. *8 Both of 32 bit version and 64 bit version are available for Windows 10, Windows 8.1, Windows 8, Windows 7, Windows server 2008. *9 Device life may vary depending on usage. And it may require exchanging our genuine parts by technicians to maintain 6 million pages based on A6 size labels

□ Backgrounding and faint print may happen. □ Please use OKI genuine consumables. 3rd party consumables may cause damage on device. □ First print time may vary depending on print data. □ An update of the latest available OS version and its detail are on OKI Data website. Please check our support page on the website. □ The latest printer driver is available on OKI Data website □ Windows is registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. □ This publication may not be reproduced in whole or in part without the express written permission of OKI Data Corporation

Consumables

Description	Material Number	EAN Code	Yield
Fuser Unit with Exit Unit	46672506	5031713071969	Approx. 150,000 pages *1
Transfer Belt Unit	46672305	5031713071976	Approx. 150,000 pages *2
Waste Toner Box	46672402	5031713071983	Approx. 25,000 pages *3
Toner Cartridge Yellow	46844011	5031713071372	Approx. 9,000 pages *4
Toner Cartridge Magenta	46844012	5031713071389	Approx. 9,000 pages *4
Toner Cartridge Cyan	46844013	5031713071396	Approx. 9,000 pages *4
Toner Cartridge Black	46844014	5031713071402	Approx. 9,000 pages *4
Toner Cartridge White	46844015	5031713071419	Approx. 4,500 pages *4

*1 Based on A6 size, 50 pages per job printing *2 Based on A6 size, 3 pages per job printing *3 Based on A6 size, 20% coverage, 3 pages per job printing *4 Based on A6 size, 20% coverage, continuous printing

□ Yield is just for your reference purpose. It may vary depending on print data, usage, Power on/off, cover open/close, etc.
 □ Toner cartridge may still consume a small amount of toner even when not printing, to maintain high print quality
 □ Toner cartridge white cannot be installed on Pro1040



OKI
Open up your dreams



Promoted and Supported by: **APSOM Infotex Ltd.**

CIN-U74899DL1993PLC054306

For more information please contact: Ph.: +91-72178 85728, email: oki.sales@apsom.com | www.apsom.com

Corporate Office: C-56/47, Institutional Area, Sector 62, Noida, U.P.-201307.